











# MATERIAL SAFETY DATA SHEET

FILE NO.: RITAR AGM VALVE REGULATED LEAD ACID BATTERY

---

## SECTION 11: TOXICOLOGICAL INFORMATION

---

### ACUTE TOXICITY (Test Results Basis and Comments):

Sulfuric acid: LD50, Rat: 2140 mg/kg

LC50, Guinea pig: 510 mg/m<sup>3</sup>

Lead: No data available for elemental lead

### SUBCHRONIC/CHRONIC TOXICITY (Test Results and Comments):

Repeated exposure to lead and lead compounds in the workplace may result in nervous system toxicity. Some toxicologists report abnormal conduction velocities in persons with blood lead levels of 50 µg/100 ml or higher. Heavy lead exposure may result in central nervous system damage, encephalopathy and damage to the blood-forming (hematopoietic) tissues.

### Additional Information

- Very little chronic toxicity data available for elemental lead.
- Lead is listed by IARC as a 2B carcinogen: possible carcinogen in humans. Arsenic is listed by IARC, ACGIH, and NTP as a carcinogen, based on studies with high doses over long periods of time. The other ingredients in this product, present at equal to or greater than 0,1% of the product, are not listed by OSHA, NTP, or IARC as suspect carcinogens.
- The 19 th Amendment to EC Directive 67/548/EEC classified lead compounds, but not lead in metal form, as possibly toxic to reproduction. Risk phrase 61: May cause harm to the unborn child, applies to lead compounds, especially soluble forms.
- The international agency for research on cancer (IARC) has classified “strong inorganic acid mist containing Sulfuric acid” as a category carcinogen, a substance that is carcinogenous to humans. This classification does not apply to liquid forms of Sulfuric acid or Sulfuric acid solutions contained within a battery. Inorganic acid mist (Sulfuric acid mist) is not generated under normal use of this product. Misuse of the product, such as overcharging, may however result in the generation of Sulfuric acid mist.

---

## SECTION 12: ECOLOGICAL INFORMATION

---

**PERSISTENCE & DEGRADABILITY:** Lead is very persistent in soils and sediments. No data available on biodegradation.

**BIOACCUMULATIVE POTENTIAL (Including Mobility):** Mobility of metallic lead between ecological compartments is low. Bioaccumulation of lead occurs in aquatic and terrestrial animals and plants, but very little bioaccumulation occurs through the food chain. Most studies have included lead compounds, not solid inorganic lead.

---

**SECTION 12: ECOLOGICAL INFORMATION** continued

---

**AQUATIC TOXICITY (Test Results & Comments):**Sulfuric acid: 24-hour LC50, fresh water fish (*Brachydanio rerio*): 82 mg/l96-hour LOEC, fresh water fish (*Cyprinus carpio*): 22 mg/l

Lead (metal): No data available

**Additional Information**

- No known effects on stratospheric ozone depletion.
- Volatile organic compounds: 0% (by Volume)
- Water Endangering Class (WGK): Not Applicable

---

**SECTION 13: DISPOSAL CONSIDERATIONS**

---

**WASTE DISPOSAL METHOD:** Dispose of as hazardous waste. If battery is leaking, place battery in a heavy-duty plastic bag. Wear acid resistant boots, faceshield, acid resistant apron, and acid resistant gloves.

Sulfuric acid: Not Applicable

Dispose off as a hazardous waste. If uncertain, call the Enirgi Power Storage representative.

DO NOT FLUSH LEAD CONTAMINATED ACID TO SEWER.

Batteries: Send to lead recycle station or contact Enirgi Power Storage representative.

**RCRA HAZARD CLASS: D001 and D008**

---

**SECTION 14: TRANSPORT INFORMATION**

---

**Name: Battery, Wet, Non-Spillable, Electric Storage****UN Number : 2800****Dangerous Goods Class : 8****Packing Group : III****Hazchem Code : 2X**

**Transport :** The Australian Dangerous Goods Code Special Provision SP238 and Special Provision A67 of the International Air Transport Association (IATA) Dangerous Goods Regulations, allows Enirgi Power Storage to transport certain non-spillable batteries as non-dangerous goods by road, rail and air. They are exempt provided they are properly packed for transport and the terminals are protected from short circuit. Contact Enirgi Power Storage for more information.



# MATERIAL SAFETY DATA SHEET

FILE NO.: RITAR AGM VALVE REGULATED LEAD ACID BATTERY

---

## SECTION 15: REGULATORY INFORMATION

---

Poison Schedule Number : S6 under "Standard for Uniform Scheduling of Drugs and Poison"

---

## SECTION 16: OTHER INFORMATION

---

**PREPARATION INFORMATION:** Prepared by Technical Officer, Enirgi Power Storage April 2011.

**DISCLAIMER:** This MSDS is offered only for information. Enirgi Power Storage provides no warranties either expressed or implied and assumes no responsibility for accuracy or completeness of the data contained herein.